

TECHNICAL DATA SHEET – Red Glazing Putty

PRODUCT: Red Glazing Putty
TECHNICAL CALLS: 1-800-321-0672



DESCRIPTION:

Red Glazing Putty is a one component, fast-drying glazing putty ideal for use under lacquer, acrylic, and synthetic finishes. The extremely fine texture of Red Glazing Putty fills pinholes, scratches and dimples on bare metal and hardened plastic fillers.

PART NUMBERS:

- 32035 Red Glazing Putty 1 Lb. Tube 12 tubes / case 13 lbs / case

PRODUCT USES:

Repairs scratches, pinholes and other imperfections both over and under primer.

TYPICAL SUBSTRATES:

- Metal • Aluminum • Aged and sanded OEM topcoats • 1K and 2K Primer



SURFACE PREPARATION:

Clean surface of all contaminants with wax & grease remover such as 1240-1. Sand surface. Clean with wax & grease remover. Dry thoroughly.

APPLICATION:

Using a squeegee or putty knife, apply Red Glazing Putty to properly prepared surface in thin, even coats. If more than one layer is necessary, allow overnight drying time before applying second layer. Maximum recommended thickness (sanded 1/32")

FINISHING:

When Red Glazing Putty is completely dry, sand with 220-400 grit prior to priming or sealing. Drying time varies depending on thickness and temperature.

TOPCOATING:

May be topcoated with primer, primer/surfacer, sealer or 1K or 2K urethane primer. Drying time varies depending on thickness and temperature.



TECHNICAL INFORMATION:

Appearance as Packaged:
Mix Ratio:
VOC

Iron oxide red paste
Ready to Use
450 g/l
3.75 lbs/gal
30 minutes (1/32" or less)

Dry Time:

ASSOCIATED MSDS: Putty: "Glazing Putty-Red-32039"

**HEALTH & SAFETY:**

Read all warnings, first aid and safety for all components before using. Keep out of reach of children and animals. Protect hands with impervious rubber gloves. Wear face, skin and eye protection. When sanding, we recommend the use of a respiratory covering device to protect from dust (MSA mask P/N 459029 with MSA cartridge 464029 or equivalent). When using power equipment, refer to power tool manufacturer's recommendations for safety equipment. USC products are for industrial use by trained professionals only.

Emergency Medical or Spill Control Information:

In U.S. or Canada call CHEMTREC at 1-800-424-9300